

1 2 3 4 5 6 7 8

APPEARANCE :

SPECIFICATION

Electrical and Acoustic Characteristics.

| | |
|--------------------------|------------------|
| Dimensions | φ 12x5.4mm |
| Rated voltage(V) | 1.5V Square Wave |
| Operating Voltage(V) | 1~2 |
| Rated Current(mA) | ≤30 |
| Coil Resistance(Ω) | 16±2 |
| Coil Impedance(Ω) | 40 |
| Sound Output at 10cm(dB) | ≥75 |
| Rated Frequency(Hz) | 2048 |
| Operating Temperature | -25~+70℃ |
| Store Temperature | -30~+85℃ |
| Case Material | PPO |
| Weight(g) | 2 |

DIMENSIONS :

FREQUENCY RESPONSE :

| | | | | |
|--|---------------------------------|---|-----------------------|--|
| <small>UNLESS OTHERWISE SPECIFIED DIMENSION ARE IN MILLIMETER AND (INCHES)</small> <small>DECIMALS .XX ±0.50 (0.02)</small> <small>ANGLES .XXX±0.025 (0.001) ±1°</small> <small>DO NOT SCALE DRAWING</small> | MATERIAL SILICONE RUBBER 60° | TIANER ECHNOLOGY(ShenZhen) http://www.itianer.com | | |
| | FINISH BLACK | TITLE Passive Electromagnetic Buzzer | | |
| THIRD ANGLE PROJEC TION | DWN BY | DATE | UNIT mm | DWG NO/ PART NO TE-HC12G-105A-H5.4 |
| | CHK BY | DATE | SCALE 5:1 | REV 01 |
| | DESIGN J.M. | DATE 09/08/22 | RELEASE DATE 2010/3/9 | SHEET |

1 2 3 4 5 6 7 8